

# Predictive Coding and Neural Communication Delays Produce Alpha-Band Oscillatory Impulse Response Functions

**Submission ID** 3000059  
**Submission Type** Oral Presentation  
**Topic** Cognitive Science  
**Status** Submitted  
**Submitter** Rufin VanRullen  
**Affiliation** CNRS CerCo

## SUBMISSION DETAILS

**Presentation Type** Either Poster or Oral Presentation

**Presentation Abstract Summary** Alpha (8-12Hz) oscillations are ubiquitous in the human brain. For example, the cross-correlation between temporally modulated white-noise visual stimuli and EEG waveforms reveals an impulse-response function (IRF) that reverberates at alpha frequency for several cycles. Yet the exact functional role of alpha rhythms in visual perception is still unknown. Here, I show that in a simplified model of visual cortex where neurons at one level seek to “explain away” the neuronal activation pattern at the previous level (i.e. “predictive coding”), alpha-band oscillatory IRFs naturally arise when neural communication delays between the two levels are taken into account. In fact, alpha oscillations are most robust when neuronal time constants and inter-areal delays are chosen with biologically plausible values –around 15-25ms and 10-15ms, respectively. The pervasive correlation between alpha rhythms and visual perception reported in numerous experimental studies could thus represent, in part, the signature of a basic computational principle: predictive coding.

**Paper Upload (PDF)** [CCN\\_VanRullen.pdf](#)

## Co-author Information

\* Presenting Author

First Name	Last Name	Affiliation	E-mail
Rufin *	VanRullen *	CNRS CerCo	rufin.vanrullen@cncs.fr

## Keywords

Keywords
alpha rhythm
oscillations

predictive coding
neural delays
time constants
impulse-response function
EEG